

Inside Screw Gate Valves

Inside screw gate valves are used underground with indicator posts attached or as roadway box valves (curb box installation). FM Approved valves are available with a variety of end connections as indicated in the listings.

Valves having Ring-Tite, Fluid-Tite or Tyton-Joint connections should be anchored in place during installation. Unless otherwise noted in the listing, these valves have 175 psi (1205 kPa) rated working pressure.

Models 5130, 5125, 5120, 5117

Resilient Seated Gate Valves. 2-1/2 through 12 inch NPS. Available with the following end connections and rated working pressures:

Model Name	Size, in. (mm)	Rated Working Pressure	End Connection
5130	2 1/2, 3, 4, 6, 8, 10, 12 (65, 80, 100, 150, 200, 250, 300)	300 psi (2070 kPa)	Grooved x Flange (ANSI B16.1 Class 125)
5125	2 1/2, 3, 4, 6, 8, 10, 12 (65, 80, 100, 150, 200, 250, 300)	250 psi (1725 kPa)	Grooved x Flange (ANSI B16.1 Class 125)
5120	2 1/2, 3, 4, 6, 8, 10, 12 (65, 80, 100, 150, 200, 250, 300)	200 psi (1375 kPa)	Grooved x Flange (ANSI B16.1 Class 125)
5117	2 1/2, 3, 4, 6, 8, 10, 12 (65, 80, 100, 150, 200, 250, 300)	175 psi (1205 kPa)	Grooved x Flange (ANSI B16.1 Class 125)

Company Name:	Ever Metal Industry Co Ltd
Company Address:	853 Kwang Fu Rd, Pa Teh City, Tao Yuen Hsien, Taiwan (R.O.C)
Company Website:	http://www.evermetalvalves.com
New/Updated Product Listing:	Yes
Listing Country:	Taiwan
Certification Type:	FM Approved