

Outside Screw and Yoke Gate Valves

Outside screw and yoke gate valves are recommended for service indoors and in pits outdoors. They are not recommended for throttling service. The stem indicates at a glance whether or not the valve is open. Smaller sizes, 3/4 through 2 in. NPS inclusive, are of bronze. Large sizes, 2 1/2 through 14 in. NPS inclusive, are of iron, bronze mounted. One manufacturer makes valves of bronze up through the 3 in. size. Unless otherwise noted in the listing, these valves have 175 psi (1205 kPa) rated working pressure.

Models 6230, 6225, 6220, 6217

Resilient Seated Gate Valves. 2-1/2 through 12 inch NPS. Available with the following end connections and rated working pressures:

Model Name	Size, in. (mm)	Rated Working Pressure	End Connection
6230	2 1/2, 3, 4, 6, 8, 10, 12 (65, 80, 100, 150, 200, 250, 300)	300 psi (2070 kPa)	Grooved x Grooved
6225	2 1/2, 3, 4, 6, 8, 10, 12 (65, 80, 100, 150, 200, 250, 300)	250 psi (1725 kPa)	Grooved x Grooved
6220	2 1/2, 3, 4, 6, 8, 10, 12 (65, 80, 100, 150, 200, 250, 300)	200 psi (1375 kPa)	Grooved x Grooved
6217	2 1/2, 3, 4, 6, 8, 10, 12 (65, 80, 100, 150, 200, 250, 300)	175 psi (1205 kPa)	Grooved x Grooved

Company Name:	Ever Metal Industry Co Ltd
Company Address:	853 Kwang Fu Rd, Pa Teh City, Tao Yuen Hsien, Taiwan (R.O.C)
Company Website:	http://www.evermetalvalves.com
New/Updated Product Listing:	Yes
Listing Country:	Taiwan
Certification Type:	FM Approved