

## Inside Screw Gate Valves

Inside screw gate valves are used underground with indicator posts attached or as roadway box valves (curb box installation). FM Approved valves are available with a variety of end connections as indicated in the listings.

Valves having Ring-Tite, Fluid-Tite or Tyton-Joint connections should be anchored in place during installation. Unless otherwise noted in the listing, these valves have 175 psi (1205 kPa) rated working pressure.

### Models 8130, 8125, 8120, 8117

Resilient Seated Gate Valves. 2-1/2 through 12 inch NPS. Available with the following end connections and rated working pressures:

Model Name	Size, in. (mm)	Rated Working Pressure	End Connection
8130	2 1/2, 3, 4, 6, 8, 10, 12 (65, 80, 100, 150, 200, 250, 300)	300 psi (2070 kPa)	Flange x Flange (ANSI B16.1 Class 125)
8125	2 1/2, 3, 4, 6, 8, 10, 12 (65, 80, 100, 150, 200, 250, 300)	250 psi (1725 kPa)	Flange x Flange (ANSI B16.1 Class 125)
8120	2 1/2, 3, 4, 6, 8, 10, 12 (65, 80, 100, 150, 200, 250, 300)	200 psi (1380 kPa)	Flange x Flange (ANSI B16.1 Class 125)
8117	2 1/2, 3, 4, 6, 8, 10, 12 (65, 80, 100, 150, 200, 250, 300)	175 psi (1205 kPa)	Flange x Flange (ANSI B16.1 Class 125)

<b>Company Name:</b>	Ever Metal Industry Co Ltd
<b>Company Address:</b>	853 Kwang Fu Rd, Pa Teh City, Tao Yuen Hsien, Taiwan (R.O.C)
<b>Company Website:</b>	<a href="http://www.evermetalvalves.com">http://www.evermetalvalves.com</a>
<b>New/Updated Product Listing:</b>	Yes
<b>Listing Country:</b>	Taiwan
<b>Certification Type:</b>	FM Approved