HMER.EX5982 Check Valves

Page Bottom

Check Valves

See General Information for Check Valves

EVER METAL INDUSTRY CO LTD

EX5982

853 Guangfu Rd Bade District Taoyuan, 334 TAIWAN

Swing type, Model 453UF, 3, 4, 6 and 8 in. sizes flanged end check valves rated pressure for 250 psig. Horizontal or vertical installation.

Swing type, Model 453UG, 3, 4, 6 and 8 in. sizes grooved end check valves rated pressure for 200 psig. Horizontal or vertical installation.

Swing type, Model 763U, 3, 4, 6, 8, 10 and 12 in. sizes flanged end check valves rated pressure for 200 psig. Horizontal or vertical installation.

Trademark and/or Tradename:

EVA

Last Updated on 2017-02-23

<u>Questions?</u> <u>Print this page</u> <u>Terms of Use</u> <u>Page Top</u>

й 2017 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".